


ERGOPLUS 500



V peak	113	Ø mm	1.0 - 1.2 - 1.6 2.0 - 2.4	X 100%	500A CO ₂ 450A Mix
------------------	-----	----------------	------------------------------	------------------	----------------------------------

	2-4 bar		1.6 l/min
--	---------	--	-----------

CODE	↔	
MB7843	3 m	EURO
MB7844	4 m	EURO
MB7845	5 m	EURO







EN 60974-7




Better performances
and protection
for your torch

UT1000157



Ø	Cu	Cu-Ni	Cu for Al	CuCrZr	Triangular Cu
0,6	MD0009-06	MD0009-36			
0,8	MD0009-08	MD0009-38	MD0009-58	MD0009-78	MD1009-08
0,9	MD0009-09				
1,0	MD0009-10	MD0009-40	MD0009-60	MD0009-80	MD1009-10
1,2	MD0009-12	MD0009-42	MD0009-62	MD0009-82	MD1009-12
1,4	MD0009-14	MD0009-44			
1,6	MD0009-16	MD0009-46	MD0009-66		



Ø	Cu	Cu-Ni	Cu for Al	CuCrZr
0,8	MD0005-08	MD0005-38	MD0005-58	
0,9	MD0005-09		MD0005-59	
1,0	MD0005-10	MD0005-40	MD0005-60	MD0005-80
1,2	MD0005-12	MD0005-42	MD0005-62	MD0005-82
1,4	MD0005-14	MD0005-44		MD0005-84
1,6	MD0005-16	MD0005-46	MD0005-66	MD0005-86
2,0	MD0005-20		MD0005-70	
2,4	MD0005-24		MD0005-74	

Ø	Triangular Cu	Triangular CuCrZr
1,0	MD1005-10	MD1005-80
1,2	MD1005-12	MD1005-82
1,6	MD1005-16	MD1005-86

